



INNOVATIVE JOURNAL OF INTELLIGENT CONTROL AND OPTIMIZATION FOR ELECTRICAL SYSTEM

Vol. 1 (2024) No. 2

Publisher by AITEKS : Aliansi ahli TEKnologi dan Sains
<https://ijcioes.org/index.php/ijcioes>

Controlling Temperature of Corn Cob Briquette Materials Using Automatic Induction Heater

Berlianti^{a*}, Efendi^a, Aulia Oktavia^a

^a. Electrical Department, Politeknik Negeri Padang, Kampus Limau Manis, Padang, 25176, Indonesia
Corresponding author: berlianti@pnp.ac.id

Abstract— Corn Briquettes can be made using direct combustion such as burning of fuel. But this method is unhealthy which can produce danger particles and smoke. One method to burn something without direct burning is using vessel reactor (oven). This research aims to build an electric oven using induction heater. Controlling oven temperature was conducted using induction heater automatically. The temperature of the oven will be controlled automatically by varied the induction heater. Oven was built of 3 (three) item induction heater and was set in 3 (three) condition. At first condition, first heater is set at 50°C. After reaches 50°C, the second induction heater is on, then at 100°C the third induction heater is on. Maximal value of temperature is 300°C. With Corn Briquette Materials is in the oven, it will be created briquette charcoal. A microcontroller based thermocouple K-Type sensor will control these condition. It achieves 50°C, 100°C and 300°C each for 1st heater, 2nd and 3rd. For 20 minutes oven temperature reaches 50°C, after next 100°C in 1 hours and reaches 300°C in 4 hours, the material reduces its weight about 20 grams in 4 hours starting in 50°C.

Keywords— Temperature; Corn Briquette Materials; Induction Heater; Automatically

*Manuscript received 8 Sep. 2024; revised 29 Oct. 2024; accepted 30 Dec. 2024. Date of publication 31 Dec. 2024.
International Journal of Intelligent Control and Optimization for Electrical System 4.0 International License.*



I. INTRODUCTION

Land area of public plantation in Indonesia in year 2023 is about 2,49 million hectare [1]. At Sumatera Barat province, land of corn area until year 2022 reaches 128.944 hectare with 853.024 tons production [2]. Many of efforts in producing corn briquette as heat sources energy is intended for economic values and persist of energy as well as sustainability. A processing to produce the corn briquette is by using direct combustion in a vessel and flushing water. But this method produced low quality charcoal with high water content and smoke with carbon dioxide (CO₂) as air pollution [3]. Based on this fact, it is needed a process in producing environmentally friendly charcoal briquette to reduce smoke. Carbonication is a process to burn corn cob in an enclosed vessel with high temperature until 500°C. This method can reduce dust level [4]. It is called pyrolysis or non direct combustion. For comparison, result of charcoal only 30% of its input material with diesel fuel direct combustion. Other for LPG (Liquid Petroleum Gas) charcoal result are 2,1 times its input but water level is 3,6 times and low heat value about 20%, high dust level 6,6 times [5] with carbon dioxide (CO₂) in the air. Alternatifly, an induction heater with increasing variabel temperature until reach optimum value for every 2 hours [6]. Combustion with wood biomass is difficult to control and burning quickly [7]. Temperature level more than 500°C caused it can break griquette quality. This research aims to built a device to burn corn cob and produce briquette with pyrolysis method attached with induction heater and controlling tempertaure. Final value will be found influence of temperature and time of burn to percentage of cahrcoal briquette result, water and dust and heater electric energy. For on-off induction heater is using thermocopel K type temperature sensor and amplifier mikrokontroller based which is layed in carbonize induction heater.

II. THE MATERIALS AND METHOD

This research is conducted in two steps. First is to build and apply sensor as well as microcontroller and induction heater. Another is measuring technique.

A. Induction Heater

An Induction heater is constructed with wound diametric, work object and heated material. These 3 (three) kind of factor are characterized the heater. It is needed to know effect of heater performance due to diameter and amount of induction turns. Induction heating is constructed and tested. According to [8] at 100°C temperature with no load it is needed 1,32 minutes to heat process with 7 cm object diameter and 7 turns. Otherwise for 7 cm diameter and 12 turns it takes 2,22 minutes. Then testing and measurement is conducted to 231 mili litre water as load. It takes 2,794 minutes. Lowest energy cosumption is about 83,89 kJ.

B. Automatic controlling

Induction heater working is controlled by temperature sensor and microcontroller arduino type. Heat temperature value is generated from enclosed heat vessel. Temperature controlling based on software arduino uno [9]. Temperature Sensor thermocouple K type is applied to this device with amplifier based on microcontroller. Block diagram of this sensor system follow as figure 1.




FIGURE 1. Block Diagram of the sensor system

Sensor is placed in the vessel with corn cob material and heated for 200°C to maximum 500°C.

At first step, 1st induction heater is on, and will reach temperature about 200°C. Then 2nd and 3rd induction heater is on until vessel temperature reaches 500°C. Controlling relay will turn off induction heater. This system suitable for the block diagram in the figure 2.




FIGURE 2. Block Diagram of the induction heater system

C. Contruction design

For vessel construction design, it should defined corn cob material capacity [10]. Density of corn cob material is about 1,31 gr/cm³ [11].

$$\text{Volume of corn cob} = \text{weight (gr)} / \text{desity (gr/cm}^3\text{)} (\text{cm}^3) \quad (1)$$

For 5 kgs corn cob then :

$$\text{Volume} = 5000 \text{ gr} / 1,31 \text{ gr/cm}^3 = 3.817 \text{ cm}^3$$

Reactor vessel will be made about 4 times of corn cob material volume.

$$\text{It is } 4 \times 3.817 = 15.267 \text{ cm}^3$$




FIGURE 3. Construction and mechanic device

III. RESULTS AND DISCUSSION

Result divide into 3 step : Induction heater circuit, controlling temperature and corn cob output.

A. Induction heater Circuit

Induction Heater circuit follow circuit diagram in figure 4.




FIGURE 4. Induction Heater Circuit

Figure 5 is real circuit of induction heater.

B. Controlling Temperature

Controlling temperature is conducted by arduino uno completed with thermocouple K type sensor with amplifier. Figure 6 is a vessel reactor



FIGURE 5. Applied of Induction Heater Circuit



FIGURE 6. Vessel Reactor

Result of the heater condition and temperature in the vessel according to table I.

TABLE I
temperature and condition of heater

No	Heater and temperature	
	1 st heater (°C)	2 nd and 3 rd heater (°C)
1	50	0
2	100	50
3	150	200
4	250	250

C. Corn cob output for briquette

Effect of the device to the corn cob material for briquette is describe as the temperature of the device to the output of corn cob weight, which is represent the level of water content as attaced in table II.

TABLE II
weight of corn cob reducing and % of water losses

No	Corn cob output for briquette		% reducing of weight
	Input (grams)	Output (grams)	
1	50	20	60
2	75	40	47
3	100	60	40
4	200	160	20
		Average	41,75

The curve of the % reducing of weight is represented in figure 7.




FIGURE 7. % reducing weight of corn cob for briquette material

Range of the reducing weight of corn cob is between 30% to 40%..

IV. CONCLUSION

After 4 hours the temperature of the vessel reactor reaches 300°C, the reducing of weight of corn cob material for briquette is between 30% to 40%. It present reducing the level of water content attent of weight losses.

ACKNOWLEDGMENT

This research was funded by a “Pusat Penelitian dan Pengabdian Masyarakat (P3M), Politeknik Negeri Padang.

REFERENCES

- [1] bps.go.id, ‘Luas Panen dan Produksi Jagung diIndonesia 2023’, bps.go.id.
- [2] sumbar.bps.go.id, ‘Luas Panen, Produksi dan Produktivitas Jagung 2020-2022’, Data BPS-sumbar.bps.go.id.
- [3] P. Rizki, M. Harahap, and M. Pasaribu, ‘PELATIHAN PEMBUATAN ARANG DAN ASAP CAIR DI KOPERASI PERTANIAN BERKAH ABADI JAYA DESA LUBUK CUIK TRAINING FOR MAKING CHARCOAL AND LIQUID SMOKE IN AGRICULTURAL KOPERASI ABADI ABADI JAYA LUBUK CUIK VILLAGE’, Semarang, 2022.
- [4] E. Sholichah, M. A. Karim, N. Afifah, B. Besar, and P. Teknologi, ‘Teknologi Untuk Mendukung Pembangunan Nasional’, 2012.
- [5] K. Ridhuan, D. Irawan, Y. Zanaria, and N. Adi, ‘41 Forum Grup Diskusi Teknologi Perguruan Tinggi Muhammadiyah (FGDT XI-PTM)’, Banda Aceh, 2018.
- [6] F. P. Januero et al., ‘RANCANG BANGUN ALAT PIROLISIS DENGAN PEMANAS INDUKSI UNTUK MENGKONVERSI LIMBAH PLASTIK MENJADI BAHAN BAKAR CAIR DITINJAU DARI TEMPERATUR TERHADAP HASIL PRODUK YANG DIHASILKAN DESIGN INDUCTION HEATER OF PYROLISIS TO CONVERT PLASTIC WASTE INTO LIQUID FUEL IN TERMS OF PRODUCT TEMPERATURE PRODUCED’, Oktober, 2020.
- [7] R. Wibowo, ‘Prosiding Seminar Nasional Publikasi Hasil-Hasil Penelitian dan Pengabdian Masyarakat “Implementasi Penelitian dan Pengabdian Masyarakat Untuk Peningkatan Kekayaan Intelektual” OPTIMASI PROSES PIROLISIS PADA PEMBUATAN BRIKET BERBAHAN AMPAS BATANG TEBU DAN SEKAM PADI’, 2017.
- [8] S. Kurniati, S. Syam, F. Lumban Bantoruan, and H. Artikel, ‘SISTEM PEMANAS INDUKSI DENGAN MENGGUNAKAN SOLENOID COIL DAN MIKROKONTROLER Info Artikel ABSTRACT’, Jurnal Media Elektro, vol. X, no. 1, Apr. 2021
- [9] M. Taufik Hidayat, SISTEM OTOMATISASI PEMANAS AIR MENGGUNAKAN SENSOR DHT11 BERBASIS ARDUINO UNO, Teknokom Vol. 6 No. 2 (2023)
- [10] Sunaryo, Rancang Ulang Incenerator Portabel Barrel Dengan Sensor Udara Pembakaran Berbasis Arduino Uno, SURYA TEKNIKA Vol. 9 No. 1, Juni 2022:353–359
- [11] Susilo, ‘Pengaruh Fraksi Volume Komposit Partikel Bonggol Jagung - Polyester untuk kampas rem’, 2017, Universitas Muhammadiyah Yogyakarta, Yogyakarta, 2018.